



PRODUCT SPECIFICATION

8" AMM Microfiltration Element Series

Model	Permeate flow GPD (m3/day)*	Pore Size
8040-TM10-QXA	10,800 (40.0)	0.2 microns

Permeate flow is based on the clean water flux at the following test conditions: 10.0 psi, 25°C, pH 8.0, 15% recovery, 15 minutes operation.

OPERATIONAL AND DESIGN DATA

Membrane Type.....	AMM Advanced Microfiltration Membrane
Configuration.....	Spiral Wound, Fiberglass Outer Wrap
Active Membrane Area.....	270 ft ² (24.8 m ²)
Recommended Applied Pressure.....	5 - 200 psi (0.3 - 14 bar)
Maximum Applied Pressure.....	600 psi (41 bar)
Recommended Operating Temperature.....	35 - 113°F (2 - 45°C)
Feedwater pH Range.....	2 - 11 continuous
Chlorine Tolerance.....	10.0 ppm
Maximum Feed Flow.....	95 GPM (22 m3/hr)
Minimum Brine Flow/Permeate Flow Ratio....	5:1
Maximum SDI (15 minutes)	5.0
Maximum Turbidity.....	1 NTU



Element Weight : 45 (20)
 Length (A) : 40.0 (1,016) Diameter (B) : 7.9 (200) Permeate Tube (C) : 1.50 (38.1)
 Units in pounds and inches, units in paranthesis in kilograms and millimetres.
 Mechanical Configuration: TriSep Style Core Tube
 Feed Spacer: 0.047" thick parallel spacer

* Permeate flow is clean water flux at standard conditions above. Not applicable for all feedwater conditions. Individual element's permeate flow may vary +/- 15%.



Engineered Membrane
SOLUTIONS